

1210G Glazing Tape

Cascade Aqua-Tech's 1210G Glazing Tape is a light density closed-cell Polyvinyl Chloride foam. This economical, general-purpose foam tape is manufactured for use in applications requiring positive seals on irregular surfaces or when flex and conformability to seal tight radius curves are critical considerations.

Characteristics common to all closed cell vinyl foam products include the ability to make a long life seal against air, moisture, light and dust penetration when compressed 30% or more.

PRODUCT ATTRIBUTES:

- Absorbs shocks, cushions, deadens sound and eliminates excess vibration.
- Provides an excellent buffer between contact surfaces.
- Die Cutting or kiss cutting available on 84# polycoated release paper or 12pt release board.
- 1210G is cast on a 5 mil super calendered kraft 83# clay coated paper.
- Gray color standard
- Sulfur-Free

THICKNESS	WIDTH	LENGTH
.079" - 1"	.250" - 57"	15' - 302'

Custom sizes are available upon request

PROPERTY	CAP Tape	Test Method
Density	8 lbs /cu.ft	ASTM D - 1667
Hardness	25 (shore 00)	ASTM D - 2240
Compression/Deflection @ 25%	2 psi	ASTM D - 1667
Compression Set @ 25%	4	ASTM D - 1667
Water Absorption	1.0% (by volume)	GTP (1)
Tensile Strength	30 psi	ASTM D - 412
Percent Elongation	150	ASTM D - 412
Thermal Conductivity (k factor)	0.27	ASTM C - 518
Recommended Service Temperature (°C) (°F)	-40- 82 -40- 180	
Recommended Application Temperature (°C) (°F)	10- 45 50- 110	